REALTECH SUPER HIGH STRENGTH

EMERGENCY SOLUTION FALSE AIR / WATER/GAS / OIL etc.



POLY STEEL



STICK



POLY STEEL (HT)

















REALTECH EMERGENCY SOLUTION FOR FALSE AIR/WATER/GAS/OIL etc.

Introduction:

It is a Metallic Filled System which gets cured within 10 minutes after mixing. It is a 100% Solid System which gets cured under high humidity, Even under water and temperature up to 5 Deg, C, It is an excellent, unmatched products for Emergency low cost repair to all under water/Humid condition.

Features & Benefit:

- Fast and Emergency repair that can be reduce the downtime.
- Fast Mixing & Easy Application.
- Will Bond to almost all material.
- The System can be used Even Underwater/High humidity, Avoids all relevant problems of hot process.

Typical Application:

Emergency Repair to Elbow, Tank, Cooling Towers, Dam, Pumps, Vessels, Pipes and Many other Emergency application.

Technical Specification:	STICK	POLY STEEL	POLY SEEL (HT)
Compressive Strength	950kg/cm ²	750kg/cm ²	900kg/cm ²
Tensile Strength	550kg/cm ²	550kg/cm ²	550kg/cm ²
Maximum Operating Temp.	150° C	300° C	650° C
Pressure Holding Capacity	10 to 12kg/cm ²	15 to 25kg/cm ²	15 to 25kg/cm ²
Working Time @ 20 Deg. C	3 to 4min.	15 to 20min.	15 to 20min.
Curing Time @ 20 Deg. C	7 to 9min.	60 min.	60 min.

Available in

Stick: Steel / Under Water / Copper / Aluminium: 24 Nos each. 65 gms (1 Box)

Poly Steel / Poly Steel (HT): 1 kg. / 5 kg. / 10 kg.



Office: H-610, Titanium City Centre, B/s. IOC Petrol Pump, 100 Feet Road, Sachin Tower, Satellite, Ahmedabad-380 015.

Regd. Off.: A/74, Ekta Tower, Vasna Barage Road, Vasna, Ahmedabad-380 007.

Ph.: (O) 08866499777 M.: 9426075044, 9426511321. E-mail: info@hitechcorporation.com Web.: www.hitechcorporation.com